

POSEIDON EDITION

COMPRESSORS FOR SPORTS & SAFETY APPLICATIONS



SPORTS & SAFETY



PE-TE/TB

MOBILE COMPRESSOR SYSTEMS WITH OPTIMISED FEATURES FOR USE IN VEHICLES AND SHIPPING

The PE-TE/TB series is designed for high FAD volumes up to 300 l/min in mobile use, and is available with a choice of electric or petrol drive. The systems are thus suitable for private use and commercial filling station operations. With compact design and functional carry frame, these compressors are easy to transport and stow in vehicles.

Their integrated oil pump enables them to be operated at inclinations of up to 15 degrees, so that this series is particularly suitable for shipping applications.

Also included is the BAUER P 21 Purification System (P 31 with PE 250-TB and PE 300-TB). This sophisticated air purification system with integrated oil and water separator and pressuriser valve reliably prevents users from inhaling air impurities¹ and provides effective protection from icing up when cartridges are changed regularly.

- › 200 - 300 l/min
- › 225 or 330 bar
- › 4 – 7.5 kW (8.8 kW petrol version)

FEATURES

- › High FAD, yet low in weight and easy to transport
- › Ideal for marine use, with interstage and afterstage cooler in stainless steel. Highly corrosion-resistant
- › Optionally available with user-friendly ultra-rugged B-TIMER mini-computer for filter cartridge monitoring



PE 300-TE with optional control unit

OPTIONAL FEATURES

- › Additional filling device for 225 or 330 bar
- › Switchover device for 225/330 bar
- › Larger Purification System P 31 (PE 200-TB, PE 250-TE and PE 300-TE only) or P 41 (PE 250-TE/TB, PE 300-TE/TB) only) for longer cartridge life
- › B-TIMER filter cartridge lifetime monitoring system
- › B-SECURUS filter cartridge saturation monitoring system (only possible with P41 and electric motor)
- › Electronic control unit (only with electric motor)
- › B-DRAIN automatic condensate drain system including automatic shut off when final pressure is reached

¹ Based on due maintenance and installation of the system in accordance with the operating manual and only where CO₂ concentrations in intake air do not exceed the predefined standard values. Local TLVs are not considered.

TECHNICAL DATA

Type	Charging rate ¹		Operating Pressure max.		Purification System	Number of Stages	Speed approx.	Drive and Motor Power		Net Weight approx.	Dimensions L x W x H
	l/min	cfm	bar	psig				Motor	kW		
PE 200-TE	200	7	330	4,780	P 21	3	1,250	Three-phase 400 V, 50 Hz ²	4.0	120	110 x 50 x 57
PE 200-TB	200	7	330	4,780	P 21	3	1,250	4-stroke petrol engine	5.9/6.6 ³	130	127 x 59 x 57
PE 250-TE	250	9	330	4,780	P 21	3	1,450	Three-phase 400 V, 50 Hz ²	5.5	130	110 x 50 x 57
PE 250-TB	250	9	330	4,780	P 31	3	1,450	4-stroke petrol engine	6.6	135	127 x 59 x 65
PE 300-TE	300	10	330	4,780	P 21	3	1,800	Three-phase 400 V, 50 Hz ²	7.5	140	110 x 50 x 57
PE 300-TB	300	10	330	4,780	P 31	3	1,800	4-stroke petrol engine	8.7	145	127 x 59 x 65

¹ Measured by cylinder filling (10 l) from 0 - 200 bar, ± 5%.

² Plug dimension: Schuko plug 16 A.

³ 6.6 kW petrol engine with option automatic condensate drain / automatic shutdown function



ACCEPTANCE AND SERVICES

MANUFACTURING IS ONLY PART OF WHAT WE DO

ISO 9001 CERTIFICATION

- › BAUER assures consistent maximum product quality by applying extensive quality control measures during and after production in line with DIN EN ISO 9001.

ACCEPTANCE TESTING

- › A factory acceptance test (FAT) or site acceptance test (SAT) in the presence of the customer or independent certifying body can be performed in addition to the standard BAUER final test.
- › Many BAUER compressors can also be produced in compliance with other standards, e.g. ASME, KHK, ATEX etc.

PACKING & PRESERVATION

- › Our compressors are packed ex works for transport by truck or air freight. We offer appropriate packing designs tailored for shipping, transport to tropical regions or long storage periods as well as short or long-term preservation.

INSTALLATION

- › Professional installation is a vital basic factor in safe operation of high-pressure systems. Our global network of branches and qualified partners provides smooth, trouble-free support in planning and implementation, wherever you are.

TRAINING

- › To ensure your staff are always up-to-date, we provide a comprehensive range of practical training courses for our customers in our own BAUER ACADEMY, where users and operators can benefit directly from our expertise.

FOR MORE DETAILS

and more accessories, see our service brochures and visit www.bauer-kompressoren.de/en/service-support.



ARE YOU INTERESTED IN OUR PRODUCTS?

CONTACT US – WE ARE HAPPY TO PROVIDE INFORMATION AND ASSISTANCE:

BAUER KOMPRESSOREN GmbH
Stäblistr. 8
81477 Munich, Germany
Tel. +49 (0) 89 78049-0
Fax +49 (0) 89 78049-167
info@bauer-kompressoren.de
bauer-kompressoren.de



BAUER KOMPRESSOREN POSEIDON EDITION EN
N39897
01.2020

Subject to technical change without notice